


C A M B R I D G E

MODEL SS640-P AND SS640-PS PORTABLE PLATFORM SCALES



Tubular stainless steel construction for strength and four point overload protection for accuracy and durability. The multi-point bumper system protects scale from shock loading and holds the platform securely in place while allowing for easy removal for cleaning, calibration or service.



Model SS640-P features four 4" USDA/FDA approved Aqualite wheels, with roller bearings and grease fittings.



Model SS640-PS features two fixed (4") and two swivel (5") USDA/FDA approved Aqualite wheels, with roller bearings, grease fittings and locking brakes.

Model SS640-P Features:

- 100 lb. to 1,000 lb. capacity.
- Low maintenance cost.
- Structural tubular Type 304 stainless steel construction.
- Environmentally protected, NTEP Certified-5,000 Division aluminum load cell.
- (4) 4" USDA/FDA approved Aqualite white plastic wheels w/ roller bearings and grease fittings.
- Heavy gauge polished stainless steel cover.
- 4 point overload protection.
- 1 part in 5,000 accuracy.
- 40" high Type 304 stainless steel indicator column with mounting plate.
- OSHA orange safety handle grips.
- Shock absorbing platform bumpers.
- Glass bead finish.

Model SS640-PS Features:

- (2) 4" USDA/FDA approved Aqualite white plastic wheels, w/ roller bearings and grease fittings. (front)
- (2) 5" swiveling USDA/FDA approved Aqualite white plastic wheels, w/ roller bearings, grease fittings and locking brakes (rear).
- 100 lb. to 1,000 lb. capacity.
- Low maintenance cost.
- Structural tubular Type 304 stainless steel construction.
- Environmentally protected, NTEP Certified-5,000 Division aluminum load cell.
- Heavy gauge polished stainless steel cover.
- 4 point overload protection.
- 1 part in 5,000 accuracy.
- 40" high Type 304 stainless steel indicator column with mounting plate.
- OSHA orange safety handle grips.
- Shock absorbing platform bumpers.
- Glass bead finish.

Approvals:



COC # 12-115A1



AM-5881-REV1



Made in USA

Members:

- THE NATIONAL CONFERENCE ON WEIGHTS AND MEASURES
- THE INTERNATIONAL SOCIETY OF WEIGHING AND MEASUREMENT

C A M B R I D G E

MODEL SS640-P AND SS640-PS PORTABLE PLATFORM SCALES

Model SS640-P & SS640-PS Options:

- Stainless steel rear push bar.
- Stainless steel or "FM" approved load cells.
- Structural tubular Type 316 stainless steel construction.

Stainless steel rear push bar.



Stainless steel or "FM" approved load cells.



Model SS640-P & SS640-PS Specifications

PLATFORM SIZE	COLUMN HEIGHT	CAPACITY	APPROX. SHIPPING WEIGHT	
			SS640-P	SS640-PS
18" x 24" x 6"	40"	100 lb. x .02 lb.	145 lb.	165 lb.
		250 lb. x .05 lb.	145 lb.	165 lb.
		500 lb. x .1 lb. *	145 lb.	165 lb.
		1,000 lb. x .2 lb. *	145 lb.	165 lb.
24" x 24" x 6"	40"	100 lb. x .02 lb.	165 lb.	185 lb.
		250 lb. x .05 lb.	165 lb.	185 lb.
		500 lb. x .1 lb. *	165 lb.	185 lb.
		1,000 lb. x .2 lb. *	165 lb.	185 lb.

* NTEP & Measurement Canada Approved

Cambridge Scale Works Battery Operated Indicators

Match your new portable platform scale to one of our battery operated indicators for the ultimate portable weighing system. Consult your distributor for package prices.



SSCSW-20AT-B *



SSCSW-10AT-B *

Distributed By:

Cambridge Scale Works, Inc. will warrant this product for one full year against defects in material and/or workmanship.

Cambridge Scale Works, Inc. • P. O. Box 670 • Honey Brook, PA 19344
(800) 292-7640 • www.cambridgescale.com

© Cambridge Scale Works, Inc. 12/2016

