

CAMBRIDGE

DIGITAL WEIGHT INDICATOR MODEL SSCSW-10 & SSCSW-10-B

Applications:

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Fork Lift Scales
- General Purpose Weighing



Standard Features Include:

- Stainless Steel NEMA 4X Enclosure with Stainless Steel Swivel Stand
- Selectable: NTEP 5,000 Divisions
Non-NTEP 20,000 Divisions
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- Clearly, Visible Center of Zero Indication on Display
- Lb/Kg Conversion
- 1 to 5 Points of Digital Calibration Available
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
 - Printer Output of Gross/Tare/Net
 - Computer Data Output
 - Scoreboard Continuous Output Alphanumeric or Numeric
 - Remote Receiver Output (RF Link)
- 120 VAC Cord with Ground
- Auto Zero Tracking
- Adjustable Motion Detection

Approvals:



COC# 06-070



CANADIAN
MEASUREMENT



MADE IN THE
USA

Cambridge Scale Works. • P O Box 670 • Honey Brook, PA 19344
(800) 292-7640 • (610) 273-7040 • www.cambridgescale.com

C A M B R I D G E

DIGITAL WEIGHT INDICATOR MODEL SSCSW-10 & SSCSW-10-B

Model SSCSW-10-B

For portable applications where battery operation is required.

Includes all standard SSCSW-10 features plus:

- Battery Operation
- Battery Charger

Optional Features:

Models SSCSW-10 & SSCSW-10-B

- 110 VAC Dry Contact Set Point
- 6 Pin Water Tight Connector
- Net Weight Totalization
- Peak Weight Hold
- Digital Scroll Tare
- RFL-Radio Frequency Link

Contact Cambridge for Additional Options



Cambridge Model SSCSW-10-B

Specifications

Description

Power - Model SSCSW-10	120 VAC Cord with Ground
Power - Model SSCSW-10-B	8 VDC 3.2 mAH* Battery
Humidity	0-90% Non-condensing
Enclosure	304 Stainless Steel NEMA 4X
Dimensions	7.5" x 4.5" x 3" without stand, +1" with stand
Resolution	NTEP: 5,000 Division, NON-NTEP: 20,000 Division
Display	High Efficient, Bright LED—6 Digits—.56" High
Input	0-15mv
Temperature	-10° to +40° Celsius
Linearity	0.001% of Full Scale
Accuracy	0.001% of Full Scale
Load Cell Supply	5VDC at 150ma (8 each 350 ohm load cells)

* (1) 350 OHM Cell - 24hrs / (4) 350 OHM Cell - 22hrs / (8) 350 OHM Cell - 15hrs

Distributed By:

Approvals:



COC# 06-070



CANADIAN
MEASUREMENT



MADE IN THE
USA

Cambridge Scale Works, Inc. will warrant this product for one full year against defects in material and/or workmanship.

Cambridge Scale Works. • P O Box 670 • Honey Brook, PA 19344
(800) 292-7640 • (610) 273-7040 • www.cambridgescale.com