

Approvals:



The National Conference on Weights and Measures
The International Society of Weighing and Measurement


CAMBRIDGI

MODEL 700-PAW-HD PORTABLE AXLE WEIGHER



| Features:

4" structural tubular steel cross-strut design equally distributes weight over entire scale surface for superior strength and durability.



Easy top access to the polycarbonate NEMA 4X junction box mounted inside the tubular steel frame. Watertight junction box connections make set-up quick and easy and allows multiple scales to be linked together.



15K & 20K "Heavy Duty" environmentally sealed load cells with captive ball leveling feet to guarantee stability and repeatability. Rock guard prevents debris from accumulating between scale and ramps.

Options: • Stainless steel load cells • Pit forms • Ramps

• WI-CELL®- wireless load cell communication

MODEL	SIZE	CAPACITY	LOAD CELLS #/CAPACITY	APPROX. SHIP WT.
700-PAW-HD	32" X 84" X 6"	30K lbs.	(4) 15K	665 lbs. ea.
700-PAW-HD	32" X 120" X 6"	30K lbs.	(4) 15K	865 lbs. ea.
700-PAW-HD	32" X 84" X 6"	35K lbs.	(4) 20K	715 lbs. ea.
700-PAW-HD	32" X 120" X 6"	35K lbs.	(4) 20K	915 lbs. ea.
700-PAW-HD	32" X 144" X 6"	40K lbs.	(6) 20K	1035 lbs. ea.
700-PAW-HD	32" X 168" X 6"	40K lbs.	(6) 20K	1730 lbs. ea.
700-PAW-HD RAMP	32" X 36" X 6"	30K-40K lbs	i.	250 lbs. ea.

Distributed By:

Cambridge Scale Works, Inc. will warrant this product for one full year against defects in material and/or workmanship. underside

topside

Model 700-PAW-HD Ramps Feature standard asphalt package constructed with formed supports and diamond tread deck plate, pre-drilled lag downs and leveling feet locators to firmly secure the scale in place.

Ramps are also available with an optional hard pack package for use on softer surfaces.

• Note: Portable Axle Weighers and ramps are sold separately.

Cambridge Scale Works, Inc. • P O Box 670 • Honey Brook, PA 19344 (800) 292-7640 • (610) 273-7040 • www.cambridgescale.com

© 2016 Cambridge Scale Works, Inc. 02/2016