

## MODEL 610-B-10AT SERIES **BENCH SCALES**



## Model 610-B-10AT Features:

- CSW-10AT check weighing indicator.
- · 10 lb. to 500 lb. capacity.
- · High strength cast aluminum subframe.
- · Plated steel hardware.
- · Heavy gauge powder coated carbon steel cover.
- · IP 65 water seal rated aluminum load cell.
- · Overload and corner protection.
- · Four vibration absorbant anti-skid, stainless steel leveling feet.
- · Rubber anti-vibration shock mounts.
- · Meets NIST HB-44 requirements for class III, 5000 division.
- · 20" powder coated column with 4" X 8" indicator mounting plate.

Model 610-B with carbon steel cover removed showing high strength cast aluminum subframe, overload protection, rubber anti-vibration shock mounts and powder coated indicator column with mounting plate.

· INCLUDES:

CSW-10AT check weighing indicator.









## **MODEL 610-B-10AT Series BENCH SCALES**

Model 610-B-10AT Specifications						
PLATFORM SIZE	CAPACITY	LOAD CELL	APPROX. SHIPPING WEIGHT			
12" x 12" x 3.5"	10 lb.	10 Kg.	30 lb.			
	25 lb.	20 Kg.	30 lb.			
	50 lb.	50 Kg.	30 lb.			
	100 lb.	75 Kg.	30 lb.			
	200 lb.	100 Kg.	30 lb.			
13" x 18" x 3.5"	10 lb.	10 Kg.	40 lb.			
	25 lb.	20 Kg.	40 lb.			
	50 lb.	50 Kg.	40 lb.			
	100 lb.	75 Kg.	40 lb.			
	200 lb.	100 Kg.	40 lb.			
18" x 18" x 4.5"	50 lb.	50 Kg.	54 lb.			
	100 lb.	100 Kg.	54 lb.			
	250 lb.	250 Kg.	54 lb.			
	500 lb.	500 Kg.	54 lb.			





## Model CSW-10AT Standard Features Include:

- Selectable NTEP 5,000 Division Non-NTEP 20,000 Division
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- 9 Pin Load Cell Connection
- · Simple No-Soldering Load Cell Connection · Auto Zero Tracking
- · Clearly, Visible Center of Zero Indication on Display
- Lb/Kg Conversion
- Keypad Calibration with Audit Trail
- Weight Totalization
- 1 to 5 Points of Digital Calibration Available

- · Span Adjustment at Increasing or Decreasing Weights
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
  - · Printer Output of Gross/Tare/Net
  - · Computer Data Output
- Scoreboard Continuous Output Alphanumeric or Numeric
- 100-240 VAC, 50/60 Hz Adapter
- Adjustable Motion Detection
- ABS Plastic Dust-Tight Enclosure with Stainless Steel Swivel Stand
- Check Weighing

Di	istributed E	Зу:			

Cambridge Scale Works, Inc. will warrant this product for one full year against defects in material and/or workmanship.